

# PRODUCT SPECIFICATIONS

## DIMENSION

Universal two-piece, snap-on aluminum trim offers non-progressive installation and is the same at the floor, ceiling, and walls – simplifying site coordination and creating a consistent aesthetic

Clear anodized or powder coat paint finish (25+ standard paint options)

Product Offering	Single Glazing	Double Glazing
Glass Thickness	3/8" or 1/2"	3/8" + 3/8", 3/8" + 1/2", 1/2" + 1/2"
Glass Type	Tempered, laminated, high-acoustic interlayer	
Profile Height	2.25"	
Profile Width	1.25"	2.70"
Max Height	10'	
Ceiling Connection	Grid or bulkhead	
Adjustability	1" total travel every 6' (+/- 1/2" at the ceiling & floor)	
Ships	Stickbuilt	
Lead Time	5-7 weeks	



Single Glazing Type	STC Rating*
3/8" Laminated	35
1/2" Laminated	36
3/8" Laminated, high acoustic interlayer	37
1/2" Laminated, high acoustic interlayer	39

\*Fully tested assembly

Double Glazing Type	STC Rating*
3/8" + 3/8" Laminated	43
3/8" + 1/2" Laminated	44
1/2" + 1/2" Laminated	45
3/8" + 1/2" Laminated, high acoustic interlayer	46

\*Fully tested assembly